



MODEL

CODE	TYPE	STRAP	THICKNESS
C2019611	CTS 200 19 mm - 3/4"	R 850 N/mm2	0.6 - 1.00 mm • 0.024" - 0.039"
		R 1100 N/mm2	0.63 - 0.8 mm • 0.025" - 0.031"
C2025611	CTS 200 25 mm - 1"	R 850 N/mm2	0.6 - 1.00 mm • 0.024" - 0.039"
		R 1100 N/mm2	0.63 - 0.8 mm • 0.025" - 0.031"
C2032611	CTS 200 32 mm - 1 1/4"	R 850 N/mm2	0.6 - 1.00 mm • 0.024" - 0.039"
		R 1100 N/mm2	0.63 - 0.8 mm • 0.025" - 0.031"

TECHNICAL SPECIFICATIONS

DIMENSIONS

Length	320 mm • 12.6"
Width	140 mm • 5.5"
Height	180 mm • 7"
Weight	2.9 kgs • 6.4 lbs

FEEDING

Pressure Range	5.5 - 7 bar • 78 - 99 psi
----------------	---------------------------

PERFORMANCE

Sealing	seal single notches
Joint strength	80% of strap strength*

* variable according to strap type



SEAL SINGLE NOTCH



Compact Technologies
15th Floor, Suite#1500 -701 West Georgia St.
Vancouver, BC, V7Y 1C6
Canada
T: +1 (604) 801-5922
F: +1 (604) 801-5911
www.compacttechnologies.com