



MODEL

| CODE | TYPE | STRAP | THICKNESS |
|----------|--------------------------------------|--------------|---------------------------------|
| C2019610 | CTS 2000 -19 mm - 3/4" - 9000N - 3B | R 850 N/mm2 | 0.6 - 1.00 mm • 0.024" - 0.039" |
| | | R 1100 N/mm2 | 0.63 - 0.8 mm • 0.025" - 0.031" |
| C2025610 | CTS 2000 25 mm - 1" - 9000N - 3B | R 850 N/mm2 | 0.6 - 1.00 mm • 0.024" - 0.039" |
| | | R 1100 N/mm2 | 0.63 - 0.8 mm • 0.025" - 0.031" |
| C2032610 | CTS 2000 32 mm - 1 1/4" - 9000N - 3B | R 850 N/mm2 | 0.6 - 1.00 mm • 0.024" - 0.039" |
| | | R 1100 N/mm2 | 0.63 - 0.8 mm • 0.025" - 0.031" |

TECHNICAL SPECIFICATIONS

DIMENSIONS

| | |
|--------|---------------------|
| Length | 430 mm • 16.9" |
| Width | 260 mm • 10.2" |
| Height | 310 mm • 12.2" |
| Weight | 10.3 kgs • 22.6 lbs |

FEEDING

| | |
|-----------------|---------------------------|
| Pressure Range | 5.5 - 7 bar • 78 - 99 psi |
| Air Consumption | 12 L/s – 25 cuf/min |

PERFORMANCE

| | |
|--------------------|---------------------------|
| Max. tension force | 9000 N - 6.5 bar - 92 psi |
| Tensioning Speed | 6 mt/m |
| Sealing | seal double notches |
| Joint strength | 80% of strap strength* |

* variable according to strap type



Compact Technologies
15th Floor, Suite#1500 -701 West Georgia St.
Vancouver, BC, V7Y 1C6
Canada
T: +1 (604) 801-5922
F: +1 (604) 801-5911
www.compacttechnologies.com