



**MODEL**

CODE	TYPE	STRAP	THICKNESS
C3092611 bu	CTS 3000 - 19/25/32 mm	R 850 N/mm2 R 1100 N/mm2	0.6 - 1.1 mm • 0.024" - 0.043"
C3092612 ch	CTS 3000 - 19/25/32 mm	R 850 N/mm2 R 1100 N/mm2	0.6 - 1.1 mm • 0.024" - 0.043"

**TECHNICAL SPECIFICATIONS**

**DIMENSIONS**

Length	340 mm • 13.4"
Width	115 mm • 4.5"
Height	90 mm • 3.5"
Weight	4.00 kg • 8.8 lbs
	4.3 Kg • 9.5 lbs*

\* with choke collar

**PERFORMANCE**

Max. tension force	15000N
Tensioning Speed	6 m/m
Sealing	seal double notches
Joint strength	80% of strap strength*

\* variable according to strap type

**FEEDING**

Pressure Range	5.5 - 7 bar • 78 - 99 psi
Air Consumption	12 L/s – 25 cuf/min



Compact Technologies  
 15th Floor, Suite#1500 -701 West Georgia St.  
 Vancouver, BC, V7Y 1C6  
 Canada  
 T: +1 (604) 801-5922  
 F: +1 (604) 801-5911  
 www.compacttechnologies.com